

D-INSP-M Inspiration

Service Pack

Medium size

PU Foam (59mm)







Built-in and flush-fitted, 2 temperatures cabinet, for

2 temperatures cabinet

serving wine

Manufactured in France

YEAR WARRANTY

Technical specifications

	Capacity	51 bottles maximum (24 white wines	s / 27 red wines)*
~ ~	Temperature	 Default setup temperature: 7°C/45° Independent temperature setting b Temperature setting range from 6 t to 52°F for the chilling upper part Temperature setting range from 13 to 64°F for the chamber lower part 	etween both compartments o 11°C / 43
Sliding shelf ACMSIW 6 bottles	Design	 2 doors options: full glass door and stainless steel glass door (Reversible integrated glass door with soft close and door stop) Lock LED screen with backlit capacitive keys 	 Inner lighting : atmosphere lighting with the light strip and 4 LEDs. (2 under the control panel + 2 under the separation shelf) 3 lighting options: permanent, open door, disabled Amber screen display
ACMSERVW 11 bottles	Accessories	 4 sliding shelves with Mains du Sommelier (possible adjustment of the position of the MDS, on the front) 2 half shelves and 1 wine service area Light oak and black glossy front Open / close locking notch 	 6 removable bottles identifiers per sliding shelf 1 erasable felt-tip marker 1 microfiber cloth 1 key ring
~	Equipement	 2 charcoal filter (with counter) 1 vacuum head, in the bottom compartment 1 insulated separation shelf, fix. (ABS material). Storage area – 6 bts 	 4 adjustable feet Low-emissivity glass and argon gas between the 2 glasses Condensate drip tray at the back
Storage shelf AXIHW 22 bottles	Regulation	 Electronic regulation Display of the real temperature inside the cabinet Display standby mode, possible 	 Visual alarms: vacuum, carbon filter malfunction Visual and audible alarms: door open, probe fault, temperature fault Automatic defrost
	Technologies	Cold production: Cords: Hot production: Hot release: Inner material: Exterior coating material:	Ventilated / Compressor R600a CE/US/UK/JA/AU/CH/C6/CN Heating element Automatic/ threshold: adjustable Stucco aluminium HDF (High Density Fiber) melamine-faced panels

Equipment **Standard shelves**











ACMSERVB 11 bottles



Half shelf ACMSI-DEMI 5 bottles

Equipment **Optional shelves**



AXIHB

22 bottles

*Traditional Bordeaux format

Insulation type:

General features

Full Glass door	Stainless steel glass door
78	78
100	100
115	115
1320-1390 x 557-594** x 597	1320-1390 x 557-594** x 597
1480 x 645 x 630	1480 x 645 x 630
	78 100 115 1320-1390 x 557-594** x 597

**With fillers

Energy efficiency & Consumption

Cords	230V-50Hz (R600a)	230V-50Hz (R600a)
Type of door	Full Glass door	Stainless steel glass door
Energy efficiency class	G	G
Annual energy consumption AEC (Kwh/year)	168	168
Sound emission (dB(A))	38	38
Sound emission Class	С	С
Ambient operating temperature (°C/°F)	12-35/54-95	12-35/54-95
Useful volume (litres)	167	

Inspiration, in a few words...

Understated & Elegant

The heart of the home, the kitchen is no longer reserved just for cooking. A place to gather and spend time together, it is open to all the family and often friends too. The kitchen has become a place where good times are shared, things are created, ideas germinate and chemistry happens...



